

# 3D- Ready DLP Projectors Available Now\*\*

## Acer

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
H5360	1,200 x 720	2,500	3,200:1	1 RGB (Mini D-Sub 15), 1 component, 1 S-video, 1 composite, 1 HDMI, 1 minijack, 1 RS-232
P1100	800 x 600	2,600	4,000:1	2 RGB (Mini D-Sub 15), 1 S-video, 1 composite, 1 HDMI, 1 minijack, 1 RS-232, USB
P1200	1,024 x 768	3,700	2,600:1	2 RGB (Mini D-Sub 15), 1 S-video, 1 composite, 1 HDMI, 1 minijack, 1 RS-232, USB
P1203	1,024 x 768	2,600	4,000:1	2 RGB (Mini D-Sub 15), 1 S-video, 1 composite, 1 HDMI, 1 minijack, 1 RS-232, USB
P1206	1,024 x 768	3,500	3,700:1	
P1303W	1,280 x 768	3,100	3,700:1	
P5205	1,024 x 768	4,000	2,500:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 1 composite, 1 HDMI, 2 minijacks (one in, one out), 1 RS-232, USB
P5271	1,024 x 768	3,100	3,700:1	2 RGB (Mini D-Sub 15), 1 S-video, 1 composite, 1 HDMI, 1 DVI, 1 minijack, 1 RS-232, USB
P5271i	1,024 x 768	3,100	3,700:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 1 composite, 1 HDMI, 1 DVI, 2 minijacks (one in, one out), 1 RS-232, USB
P5290	1,024 x 768	4,000	3,700:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 1 HDMI, 1 DVI, 2 minijacks, 1 RS-232, USB
S5200	1,024 x 768	3,000	2,500:1	
X1130P	800 x 600	2,500	3,000:1	1 RGB (Mini D-Sub 15), 1 S-video, 1 composite, 1 RS-232
X1161	800 x 600	2,500	4,000:1	1 RGB (Mini D-Sub 15), 1 S-video, 1 composite, USB
X1261	1,024 x 768	2,500	3,700:1	1 RGB (Mini D-Sub 15), 1 component, 1 S-video, 1 composite, 1 minijack, 1 RS-232

\*\* Check [www.dlp.com](http://www.dlp.com) for updates to this list

\* Specifications reported by manufacturers may be estimations or approximations.

## BenQ

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
MP670	1,024 x 768	3,200	3,000:1	2 RGB (Mini D-Sub 15, one in, one out), 1 S-video, 1 composite, 1 HDMI, 2 stereo minijacks (one in, one out), stereo RCA audio, 1 RS-232, USB
MP772 ST	1,024 x 768	2,500	3,500:1	2 RGB (Mini D-Sub 15, one in, one out), 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), 1 RS-232
MP776	1,024 x 768	3,500	4,000:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 1 HDMI, 2 stereo minijacks (one in, one out), stereo RCA audio, 1 RS-232
MP776 ST	1,024 x 768	3,500	3,500:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 1 HDMI, 2 stereo minijacks (one in, one out), stereo RCA audio, 1 RS-232
MP777	1,024 x 768	4,000	4,000:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 1 HDMI, 2 stereo minijacks (one in, one out), stereo RCA audio, 1 RS-232
MP782 ST	1,280 x 800	2,500	3,500:1	2 RGB (Mini D-Sub 15, one in, one out), DVI-D, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), stereo RCA audio, 1 RS-232

## Dell

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
1510X	1,024 x 768	3,000	2,100:1	3 RGB (Mini D-Sub 15, two in, one out), HDMI, 1 S-video, 1 composite, 1 stereo minijack, stereo RCA audio, 1 mic input, USB
1610HD	1,280 x 800	3,000	2,100:1	3 RGB (Mini D-Sub 15, two in, one out), HDMI, 1 S-video, 1 composite, 1 stereo minijack, stereo RCA audio, 1 mic input, RS-232, USB
M210X	1,024 x 768	2,000	2,100:1	1 RGB (Mini D-Sub 15), HDMI, 1 S-video, 1 composite, 1 minijack, USB
M410HD	1,280 x 800	2,000	2,100:1	1 RGB (Mini D-Sub 15), HDMI, 1 S-video, 1 composite, 1 minijack, USB

## Eiki

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*
EIP D450	1024 x 768	4500	2500:1
EIP XSP2500	1024 x 768	2500	1600:1

\* Specifications reported by manufacturers may be estimations or approximations.

## InFocus

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
IN2112	800 x 600	3,000	2,100:1	2 RGB (Mini D-Sub 15), 2 component, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), 1 RS-232, USB
IN2114	1,024 x 768	3,000	2,100:1	2 RGB (Mini D-Sub 15), 2 component, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), 1 RS-232, USB
IN2116	1,280 x 800	3,000	2,100:1	2 RGB (Mini D-Sub 15), 2 component, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), 1 RS-232, USB
IN3114	1,024 x 768	3,500	2,100:1	2 RGB (Mini D-Sub 15), 2 component, HDMI, USB DisplayLink, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), 1 RS-232, USB
IN3116	1,280 x 800	3,500	2,100:1	2 RGB (Mini D-Sub 15), 2 component, HDMI, USB DisplayLink, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), 1 RS-232, USB

## Mitsubishi

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
XD600	1,024 x 768	4,500	2,000:1	1 RGB (Mini D-Sub 15), HDMI, 1 S-video, 1 composite, 1 stereo minijack, 1 RS-232

## NEC

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
NP115	800 x 600	2,500	2,000:1	2 RGB (Mini D-Sub 15, one in, one out), 1 S-video, 1 composite, 1 stereo minijack, stereo RCA audio, 1 RS-232
NP210	1,024 x 768	2,200	2,000:1	1 RGB (Mini D-Sub 15), 1 S-video, 1 composite, 1 stereo minijack, 1 RS-232
NP215	1,024 x 768	2,500	2,000:1	1 RGB (Mini D-Sub 15), 1 S-video, 1 composite, 1 stereo minijack, 1 RS-232

## Promethean

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
PRM25	1280 x 800	2000		

## Sanyo

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
PDG-DWL2500J	1280 x 800	2,500	2,000:1	

\* Specifications reported by manufacturers may be estimations or approximations.

## Sharp

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
PG-D2500X	1,024 x 768	2,500	1,100:1	1 RGB (Mini D-Sub 15), HDMI, DVI-I, 1 S-video, 1 composite, USB, 1 RS-232
PG-D2710X	1,024 x 768	2,700	2,000:1	1 RGB (Mini D-Sub 15), HDMI, DVI-I, 1 S-video, 1 composite, USB, 1 RS-232
PG-D3010X	1,024 x 768	3,000	2,000:1	1 RGB (Mini D-Sub 15), HDMI, DVI-I, 1 S-video, 1 composite, USB, 1 RS-232
PG-D3510X	1,024 x 768	3,500	2,000:1	1 RGB (Mini D-Sub 15), HDMI, DVI-I, 1 S-video, 1 composite, USB, 1 RS-232
PG-D40W3D	1,280 x 800	4,000	2,500:1	2 RGB (Mini D-Sub 15, one in, one out), HDMI, DVH, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), stereo RCA audio, USB, 1 RS-232
PG-D45X3D	1,024 x 768	4,500	2,500:1	2 RGB (Mini D-Sub 15, one in, one out), HDMI, DVH, 1 S-video, 1 composite, 2 stereo minijacks (one in, one out), stereo RCA audio, USB, 1 RS-232
XR-55X	1,024 x 768	2,700	2,000:1	2 RGB (Mini D-Sub 15, one in, one out), 1 S-video, 1 composite, 1 stereo minijack, stereo RCA audio, 1 RS-232, USB

## Smart

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
UF65	1040 x 768	2000	2,000:1	
UF65w	1280 x 800	2000	2,000:1	

## Viewsonic

Model	Resolution (Pixels, W x H)*	Brightness (Lumens)*	Contrast Ratio*	I/O
PJD5112	800 x 600	2,600	2,000:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 2 stereo minijacks (one in, one out), 1 RS-232
PJD6211	1,024 x 768	2,500	2,000:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 2 stereo minijacks (one in, one out), 1 RS-232
PJD6221	1,024 x 768	2,700	2,800:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, stereo minijack, 1 RS-232
PJD6241	1,024 x 768B	3,200	3,200:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 3 stereo minijacks (two in, one out), 1 RS-232, USB
PJD6251	1,024 x 768	3,700	2,000:1	3 RGB (Mini D-Sub 15, two in, one out), HDMI, 1 S-video, 2 stereo minijacks (one in, one out), 1 RS-232
PJD6531W	1,280 x 800	3,000	2,000:1	3 RGB (Mini D-Sub 15, two in, one out), HDMI, 1 S-video, 2 stereo minijacks (one in, one out), 1 RS-232
PJD6381	1,024 x 768	2,500	2,400:1	3 RGB (Mini D-Sub 15, two in, one out), HDMI, 1 S-video, 2 stereo minijacks (one in, one out), 1 RS-232

\* Specifications reported by manufacturers may be estimations or approximations.

## Vivitek

---

<b>Model</b>	<b>Resolution (Pixels, W x H)*</b>	<b>Brightness (Lumens)*</b>	<b>Contrast Ratio*</b>	<b>I/O</b>
D511	1,024 x 768	2,600	2,300:1	1 RGB (Mini D-Sub 15), HDMI, 1 S-video, 1 composite, stereo minijack, 1 RS-232, USB
D535	1,024 x 768	3,200	2,300:1	1 RGB (Mini D-Sub 15), HDMI, 1 S-video, 1 composite, stereo minijack, stereo RCA audio, 1 RS-232, USB
D835	1,024 x 768	3,200	2,500:1	3 RGB (Mini D-Sub 15, two in, one out), 1 S-video, 2 stereo minijacks (one in, one out), stereo RCA audio, 1 RS-232, USB
D837	1,024 x 768	3,200	2,500:1	3 RGB (Mini D-Sub 15, two in, one out), HDMI, 1 S-video, 2 stereo minijacks (one in, one out), stereo RCA audio, 1 RS-232, USB

\* Specifications reported by manufacturers may be estimations or approximations.